

Straight screw connections

Nickel plated Brass

With conical thread

pneuparts
.com

TECHNICAL FEATURES

Bedrijfsdruk:

-0,95 tot 20 bar

Temperatuurbereik:

-20°C tot max. +80°C, met FKM-afdichting tot max. +150°

Materiaal:

Messing vernikkeld



ARTICLE NUMBER	THREAD	HOSE/TUBE	THREAD TYPE
SC1853CONMSV	R 1/8"	5x3	Conical
SC184CONMSV	R 1/8"	6x4	Conical
SC186CONMSV	R 1/8"	8x6	Conical
SC144CONMSV	R 1/4"	6x4	Conical
SC146CONMSV	R 1/4"	8x6	Conical
SC148CONMSV	R 1/4"	10x8	Conical

ARTICLE NUMBER	THREAD	HOSE/TUBE	THREAD TYPE
SC384CONMSV	R 3/8"	6x4	Conical
SC386CONMSV	R 3/8"	8x6	Conical
SC388CONMSV	R 3/8"	10x8	Conical
SC3810CONMSV	R 3/8"	12x10	Conical
SC128CONMSV	R 1/2"	10x8	Conical

Pneuparts.com

Florijn 10 b/c
5751 PC Deurne
The Netherlands

Phone: +31 (0)493 763 993

info@pneuparts.com
www.pneuparts.com