

# Steel push-in coupling

## reducer

Temperature range: -20°C to  
max. +70°C

Operating pressure: up to max.  
18 bar

Vacuum:  
-99


### PGJ

Steel verloopkoppeling


Reducer

Réduction

Reduzierstück



Type	Ø Tubo	D1	D2	L1	g $\Delta$
PGJ0604TL	4	6	10	31,5	1,7
PGJ0804TL	4	8	10	32,5	2
PGJ1004TL	4	10	10	34,5	3
PGJ 0806TL	6	8	12	37	2,6
PGJ1006TL	6	10	12	37	3,1
PGJ1206TL	6	12	12	39	3,9
PGJ1008TL	8	10	14	39,5	3,7
PGJ1208TL	8	12	14	41,5	4,4
PGJ1210TL	10	12	16	45	5,3
PGJ1410TL	10	14	16	45	6,2
PGJ1412TL	12	14	19	47	7,1



Type	Ø Tubo	D1	D2	L1	g $\Delta$
PGJ0406TL	6	4	12	34	2,1
PGJ0608TL	8	6	14	36,5	2,9

**Pneuparts.com**

Florijn 10 b/c  
5751 PC Deurne  
Nederland

+31 (0)493 763 99  
info@pneuparts.com  
www.pneuparts.com