

# Elbow push-in coupling, extended

Male thread

Temperature range: -20°C to  
max. +70°C

Operating pressure: up to max.  
18 bar

Vacuum:  
-99


## PLL

Verlengde draaibare knie  
inschroefkoppeling buitendraad

Swivelling extended elbow fitting,  
male, parallel

Coude long tournant,  
mâle cylindrique

Verlängerte Winkelverschraubung,  
drehbar und zylindrisch



Type	Ø Tub	D1	D2	L1	L2	L3	CH	gΔΔ
PLL04M5TL	4	M5x0,8	10	4	23,8	15,5	9	9,1
PLL04G18TL	4	G1/8	10	5	24	15,5	13	10,2
PLL04G14TL	4	G1/4	10	6,5	26	15,5	16	13,7
PLL06M5TL	6	M5x0,8	12	4	29,8	20	12	20,8
PLL06G18TL	6	G1/8	12	5	31,8	20	13	19,6
PLL06G14TL	6	G1/4	12	6,5	33,8	20	16	20,5
PLL08G18TL	8	G1/8	14	5	32,5	21,5	13	20
PLL08G14TL	8	G1/4	14	6,5	34,5	21,5	16	20,9
PLL08G38TL	8	G3/8	14	7	36	21,5	20	29,4
PLL10G14TL	10	G1/4	16	6,5	36,9	24	16	32,3
PLL10G38TL	10	G3/8	16	7	38,9	24	20	36,8