

Mini safety valves

Adjustable, not component tested

Materials:

Body: brass, seal: NBR (G 1/4": FKM)

Temperature range:

-10°C to max. +100°C (G 1/4": -20°C to max.+200°C)

Media:

Compressed air and other non-toxic non-inflammable gases, blown-off freely



Article code	Thread	Reaction pressure	Blow-off capacity	Temp. range °C	Orifice (DN)
ASV146	G 1/4"	1 - 6.5 bar	1.3 - 4.9 m3/h	20 tot +200 °C	5 mm
ASV1410	G 1/4"	6.5 - 10 bar	4.9 - 7.2 m3/h	20 tot +200 °C	5 mm
ASV1413	G 1/4"	10 - 13 bar	7.2 - 9.2 m3/h	20 tot +200 °C	5 mm
ASV386	G 3/8"	1 - 6 bar	76 - 248 m3/h	10 tot +100 °C	10 mm
ASV388	G 3/8"	4 - 8 bar	176 - 320 m3/h	10 tot +100 °C	10 mm
ASV3812	G 3/8"	8 - 12 bar	320 - 464 m3/h	10 tot +100 °C	10 mm
ASV3816	G 3/8"	12 - 16 bar	76 - 248 m3/h	10 tot +100 °C	10 mm
ASV126	G 1/2"	1 - 6 bar	464 - 609 m3/h	10 tot +100 °C	10 mm
ASV1212	G 1/2"	4 - 12 bar	76 - 248 m3/h	10 tot +100 °C	10 mm
ASV1216	G 1/2"	12 - 16 bar	464 - 609 m3/h	10 tot +100 °C	10 mm