

# Straight push-in coupling

Tapered thread

**Temperature range:**  
-20°C to max. +80°C

**Operating pressure:**  
up to max. 20 bar

**Vacuum:**  
-99


## PC..C

Rechte push-in fitting  
conische buitendraad

Straight screw connection  
conical male thread

Raccordement droit à vis  
filetage mâle conique

Gerade Schraubverbindung  
konisches Außengewinde



Type	Tube	D1	D2	L1	L2	CH1	CH2
PC04C18TL	4	R1/8	M10x1	14,5	17	7	26
PC04C14TL	4	R1/8	M12x1,5	14,5	17	8,5	27,5
PC06C18TL	6	R1/8	M14x1,5	14,5	17	8,5	27
PC06C14TL	6	R1/8	M16x1,5	14,5	20	8,5	25
PC06C38TL	6	R1/8	M10x1	16,5	19	7	31
PC08C18TL	8	R1/8	M12x1,5	16,5	19	8,5	32,5
PC08C14TL	8	R1/8	M14x1,5	16,5	19	8,5	27,5
PC08C38TL	8	R1/8	M16x1,5	16,5	20	8,5	27
PC08C12TL	8	R1/8	M22x1,5	16,5	25,5	8,5	23
PC10C18TL	10	R1/8	M12x1,5	18,5	21	8,5	34,7
PC10C14TL	10	R1/8	M14x1,5	18,5	21	8,5	34,7
PC10C38TL	10	R1/8	M16x1,5	18,5	22	8,5	29,5
PC10C12TL	10	R1/8	M22x1,5	18,5	25,5	8,5	25,5
PC12C14TL	12	R1/8	M12x1,5	20,5	23	8,5	35,5
PC12C38TL	12	R1/8	M14x1,5	20,5	23	8,5	35,5
PC12C12TL	12	R1/8	M16x1,5	20,5	23	8,5	34,5

**Pneuparts.com**

Florijn 10 b/c  
5751 PC Deurne  
Nederland

+31 (0)493 763 99  
info@pneuparts.com  
www.pneuparts.com