

T Push-in coupling

Male thread

Temperature range: -20°C to
max. +70°C

Operating pressure: up to max.
18 bar

Vacuum:
-99


PD

Zij-inschroef T-koppeling

Lateral run tee fitting, parallel

Raccord à té latéral cylindrique, tournant

T-
Schwenkverschraubung
, zylindrisch



Type	Ø Tubo	D1	D2	L1	L2	L3	CH	g _A
PD04M5TL	4	M5x0,8	10	4	14,8	15,5	9	5,6
PD04G18TL	4	G1/8	10	5	15	15,5	13	8,1
PD04G14TL	4	G1/4	10	6,5	17	15,5	16	13
PD06M5TL	6	M5x0,8	12	4	15,3	20	12	10,3
PD06G18TL	6	G1/8	12	5	17,3	20	12	9,9
PD06G14TL	6	G1/4	12	6,5	19,3	20	15	13,9
PD08G18TL	8	G1/8	14	5	18	21,5	12	10,7
PD08G14TL	8	G1/4	14	6,5	20	21,5	15	14,7
PD08G38TL	8	G3/8	14	7	21,5	21,5	20	27,4
PD10G14TL	10	G1/4	16	6,5	21,5	24	16	20
PD10G38TL	10	G3/8	16	7	23,5	24	20	25,1