

Pressure regulator

pneuparts
.com

Up to 12160 l/min

Self-relieving pressure regulator, PN 40

Version:

Self-relieving pressure regulator

Materials:

Body: brass (DR 8740 and DR 8840: gravity die cast aluminium),
diaphragms and seals: NBR

Temperature range:

-10°C bis +90°C

Input pressure:

max. 40 bar

Pressure gauge connection:

G 1/4"

Switch panel thread:

DR 1140: M 20 x 1,5, DR 3340: M 28 x 1,5

Media:


Oiled and unoled compressed air, neutral gasses

Scope of delivery:

Pressure regulator incl. 50 mm pressure gauge

Benefits:

Automatic ventilation in case of overpressure on the secondary side



** Check out the next page to orde*

Pneuparts.com
Florijn 10 b/c
5751 PC Deurne
Nederland

Phone: +31 (0)493 763 993
info@pneuparts.com
www.pneuparts.com

BTW: NL8209.12.931B01
KvK: 17126382
Swift: RABONL24
IBAN: NL23RABO01036.31240

HOW TO ORDER: Click on the article numbers to order

G 1/4" Thread, Flow: 430 l/min, Brass MS, 40 PN

Article nr.	HPR11403G	HPR11406G	HPR1140G	HPR114016G	HPR114025G
bar:	0.5 - 3 bar	0.5 - 6 bar	0.5 - 10 bar	0.5 - 16 bar	0.5 - 25 bar

G 1/2" Thread, Flow: 1250 l/min, Brass MS, 40 PN

Article nr.	HPR33403G	HPR33406G	HPR3340G	HPR334016G	HPR334025G
bar:	0.5 - 3 bar	0.5 - 6 bar	0.5 - 10 bar	0.5 - 16 bar	0.5 - 25 bar

G 3/4" Thread, Flow: 7830 l/min, Brass MS, 40 PN

Article nr.	HPR54403G	HPR54406G	HPR5440G	HPR544016G	HPR544025G
bar:	0.5 - 3 bar	0.5 - 6 bar	0.5 - 10 bar	0.5 - 16 bar	0.5 - 25 bar

G 1" Thread, Flow: 7830 l/min, Brass MS, 40 PN

Article nr.	HPR55403G	HPR55406G	HPR5540G	HPR554016G	HPR554025G
bar:	0.5 - 3 bar	0.5 - 6 bar	0.5 - 10 bar	0.5 - 16 bar	0.5 - 25 bar

G 1 1/4" Thread, Flow: 12160 l/min, Brass MS, 40 PN

Article nr.	HPR76403G	HPR76406G	HPR7640G	HPR764016G	HPR764025G
bar:	0.5 - 3 bar	0.5 - 6 bar	0.5 - 10 bar	0.5 - 16 bar	0.5 - 25 bar

G 1 1/2" Thread, Flow: 7830 l/min, Brass MS, 40 PN

Article nr.	HPR77403G	HPR77406G	HPR7740G	HPR774016G	HPR774025G
bar:	0.5 - 3 bar	0.5 - 6 bar	0.5 - 10 bar	0.5 - 16 bar	0.5 - 25 bar