

Swivel knee push-in coupling

Male Thread

Temperature range:
-20°C to max. +80°C

Operating pressure:
up to max. 18 bar


Vacuum:
-99

PL

Draaibare knie inschroefkoppeling
buitendraad

Parallel swivelling elbow, male

Raccord à coude tournant, mâle
cylindrique



Type	Ø Tu	D1	D2	L1	L2	L3	CH	g
PL04M5TL	4	M5x0,8	10	4	14,8	15,5	9	4,6
PL04G18TL	4	G1/8	10	5	15	15,5	13	7,1
PL04G14TL	4	G1/4	10	6,5	17	15,5	16	11,1
PL06M5TL	6	M5x0,8	12	4	15,3	20	12	7,9
PL06G18TL	6	G1/8	12	5	17,3	20	12	8,4
PL06G14TL	6	G1/4	12	6,5	19,3	20	15	12,5
PL08G18TL	8	G1/8	14	5	18	21,5	12	8,8
PL08G14TL	8	G1/4	14	6,5	20	21,5	15	13
PL08G38TL	8	G3/8	14	7	21,5	21,5	20	21,4
PL10G14TL	10	G1/4	16	6,5	21,5	24	16	15,6
PL10G38TL	10	G3/8	16	6,5	23,5	24	20	22,8
PL12G38TL	12	G3/8	19	7	24	28,5	20	27,2
PL12G12TL	12	G1/2	19	8,5	28,5	28,5	20	34,9
PL14G38TL	14	G3/8	22,5	7	25	32,3	20	28,8
PL14G12TL	14	G1/2	22,5	8,5	29,5	32,3	20	36,5