

Mini safety valves

Adjustable 0.5 - 60 bar

Stainless steel 303 (1.4305)

TECHNICAL FEATURES

Materials:

Brass

* Optional: Stainless steel 303, (1.4305)

Temperature range:

-10°C to +180°C

Media:

Compressed air and other non-toxic, non-flammable gases, vent freely

Seal:

Standard viton seal

* Optional: EPDM, NBR or Silicone



ARTICLE NUMBER	Thread	Reaction pressure (Bar)	Blow-off capacity (m3 / hour)	C	D	SW
AMSV181SS	G 1/8"	0.5 - 1	to 50	27	7	16
AMSV184SS	G 1/8"	1 - 4	to 200	27	7	16
AMSV187SS	G 1/8"	3 - 7	to 350	27	7	16
AMSV1812SS	G 1/8"	6 - 12	to 650	27	7	16
AMSV1818SS	G 1/8"	10 - 18	to 870	27	7	16
AMSV1832SS	G 1/8"	16 - 32	to 1600	27	7	16
AMSV1860SS	G 1/8"	30 - 60	to 3000	27	7	16
AMSV141SS	G 1/4"	0.5 - 1	to 50	27	7	16
AMSV144SS	G 1/4"	1 - 4	to 200	27	7	16
AMSV147SS	G 1/4"	3 - 7	to 350	27	7	16
AMSV1412SS	G 1/4"	6 - 12	to 650	27	7	16
AMSV1418SS	G 1/4"	10 - 18	to 870	27	7	16
AMSV1432SS	G 1/4"	16 - 32	to 1600	27	7	16
AMSV1460SS	G 1/4"	30 - 60	to 3000	27	7	16

