

Knee push-in coupling

Tapered Thread

Temperature range:
-20°C to max. +80°C

Operating pressure:
up to max. 18 bar

Vacuum:
-99


PL

Knie inschroefkoppeling
conisch, buitendraad

Taper swivelling elbow fitting, male

Raccord à coude tournant, mâle conique

Schwenkbare
Winkelverschraubung, kegelig



Type	Ø Tub	D1	D2	L1	L2	L3	CH	g Δ
PL04C18TL	4	R1/8	10	7,5	17	15,5	10	6,4
PL04C14TL	4	R1/4	10	11	20,5	15,5	14	11,5
PL06C18TL	6	R1/8	12	7,5	18,8	20	12	8,4
PL06C14TL	6	R1/4	12	11	23,3	20	14	13,6
PL08C18TL	8	R1/8	14	7,5	19,5	21,5	12	9
PL08C14TL	8	R1/4	14	11	24	21,5	14	14,1
PL08C38TL	8	R3/8	14	11,5	24,5	21,5	17	19
PL10C14TL	10	R1/4	16	11	25,5	24	16	17,3
PL10C38TL	10	R3/8	16	11,5	26,5	24	17	21,7
PL12C38TL	12	R3/8	19	11,5	28,5	28,5	20	32,8
PL12C12TL	12	R1/2	19	14	31,5	28,5	22	41,4
PL14C38TL	14	R3/8	22,5	11,5	29,5	32,3	20	34,6
PL14C12TL	14	R1/2	22,5	14	32,5	32,3	22	43,2