

# Festo solenoid valve

## G 1/4", Model series VUVS LK25

### Data sheet

**Materials**

Body: Aluminium/ plastic, seals: NBR

**Temperature range:**

-5 ° C to + 50 ° C

**Operating pressure:**

1,5 - 8 bar

**Media:**

Oiled and oil-free compressed air

**Switching time:**

<22 ms

**Control voltages:**

24 V=

**Voltage tolerance:**

± 10%

**Energy consumption:**

2.6 W

**Protection class (VDE 0470/EN60529):**

IP 65, plug size 1

**Warning:**

Valve plug is not included in the scope of delivery. Please order separately! Article number: SPSV0D0C

\* Pneumatic spring



| Article nr.           | Function          | Thread  | Workload  | Orifice (DN) | Voltage |
|-----------------------|-------------------|---------|-----------|--------------|---------|
| VUVSLK25M32CADG141B2S | 3/2 NC            | G 1/4 " | 1.5-8 bar | 1000 L/min.  | 24V=    |
| VUVSLK25M52ADG141B2S  | 5/2 spring return | G 1/4 " | 1.5-8 bar | 1000 L/min.  | 24V=    |
| VUVSLK25B52DG141B2S   | 5/2 impulse       | G 1/4 " | 1.5-8 bar | 1000 L/min.  | 24V=    |